



# Disabled Refuge Call System Handset (Type A) (EVC/SR)

Revision 2, 10<sup>th</sup> August 2009

A Fire Telephone and Disabled Refuge remote version can be supplied as an alternative to having two systems. Both flush and surface mounting units can be supplied. The surface unit has a red leatherette (RAL9001) mild steel back box. A call is made by simply lifting the remote handset (Red). This will illuminate the switch on the master control panel as a conventional fire telephone call. A duplex configuration similar to standard telephone will be initiated. The front face of the surface enclosure has a sloped frame (see dimensions below).

Dimensions: -	
Surface	332mm (H) x 182mm (W) x 96mm (D Top), 81mm (D Bottom)
Flush	372mm (H) x 232mm (W) x 1.5mm (D)
Back box behind flange	332mm (H) x 182mm (W) x 77mm (D)



EVC-SR



EVC-FR

Power Consumption: -	
Quiescent	6 mA @ 24 volts
Calling	30 mA @ 24 volts
Active	40 mA @ 24 volts

**Cameo Systems Limited**

29 Haviland Road, Ferndown Industrial Estate, Wimborne, Dorset, BH21 7SA  
 Tel : 01202 892088, Fax : 01202 861449  
 E-mail : [sales@cameosystems.co.uk](mailto:sales@cameosystems.co.uk) Web : [www.cameosystems.co.uk](http://www.cameosystems.co.uk)