



## Disabled Refuge Call System Handset (Type A) (RCO/SR)

Revision 2, 7<sup>th</sup> April 2009

A remote telephone handset outstation can be supplied. This can be provided in both surface and flush mounting. This unit is finished in a green leatherette (BS4800 14E53) paint with a polycarbonate front label and houses a grey handset. Operationally this unit is identical to our Fire Telephone range. By simply lifting the remote handset a call is made automatically to the central control panel. A duplex configuration similar to standard telephone will be initiated. The front face of the surface enclosure has a sloped frame (see dimensions below).

Dimensions: -	
Surface	329mm (H) x 182mm (W) x 96mm (D Top), 81mm (D Bottom)
Flush	379mm (H) x 232mm (W) x 1.5mm (D)
Back box behind flange	332mm (H) x 182mm (W) x 77mm (D)

Available in RED



Power Consumption: -	
Quiescent	6 mA @ 24 volts
Calling	30 mA @ 24 volts
Active	40 mA @ 24 volts

### Cameo Systems Limited

29 Haviland Road, Ferndown Industrial Estate, Wimborne, Dorset, BH21 7SA

Tel : 01202 892088, Fax : 01202 861449

E-mail : [sales@cameosystems.co.uk](mailto:sales@cameosystems.co.uk) Web : [www.cameosystems.co.uk](http://www.cameosystems.co.uk)