ORB-R-RS8-OLED-F or ORB-L-RS8-OLED-F

Product Description

The Orbital RS8 is an eight way combined disabled refuge and disabled toilet alarm system. Stainless steel flush enclosure with black screen print and glazed lockable door. The master panel can answer or call out by pressing the separate call switches and indications for each disabled refuge location. The built in alphanumeric blue OLED screen for disabled refuge zone description and '32' disabled toilet alarm zone indication. Group or all call can also be selected. Once connected a clear full duplex audio conversation can take place. The call is ended by replacing the master handset. The disabled refuge outstations are radially wired in '2' core '1.5'mm enhanced fire rated cable or as a loop wired '4' core '1.5'mm enhanced fire rated cable. A volt free changeover contact is provided for remote call in and fault reporting. A fire panel inhibit input is also fitted as standard. Battery support 24 + 3 hours. Fully compliant to BS5839 Pt9 and CE 2019 certified. A simple two core cable should be wired from the disabled toilet PSU/Sounder unit to the nearby disabled refuge outstation. The refuge outstation back box is supplied with terminals for this connection.



Dimensions

Flush back box 361mm (H) x 460mm (W) x 110mm (D)

Flushing Flange 410mm (H) x 510mm (W) x 1.5mm (D)

Category

Disabled Refuge Call	Radial - ORB-R-RS8-OLED-F	Loop - ORB-L-RS8-OLED-F